


# Portability Issues for ECS Science Software Integration Narayan Prasad

Science Software Integration and Test Workshop, Landover, MD April 18, 1995


# **Major Incompatibilities**



#### Due to:

- Complexity introduced by byte ordering
- Word size in 32- and 64-bit machines
  - limitations
  - differences
- Differences in operating system
- Language extensions

## **Byte Ordering**



#### **Architectures**

- Little-endian (Digital, MasPar, etc.) High byte on the right
- Big-endian (HP, SGI, SUN, IBM, Cray, etc.) High byte on the left


#### **Implications**

- For high-level source code no modification is necessary; only need recompilation and relinking
- For data in packed binary format, need code modifications when porting across different byte-ordered architectures
- Binary data require byte reordering

#### **Compiler options**

- DEC Alpha has a switch (for Fortran only) to convert big-endian to littleendian and vice-versa
- No such option is available on big-endian machines to accommodate code from little-endian architectures

### **Word Size**




#### Limitations

- Cray is word addressable (minimum is 8 bytes)
  - need bitwise operators manipulating sizes less than 8 bytes (can make porting difficult)
- SGI Power Challenge is byte addressable (minimum is 1 byte)

#### **Differences**

- differences in data type sizes (e.g. SGI Challenge and SGI Power Challenge)
  - long int, pointer (32 bits on 32-bit machines; 64 bits on 64-bit machines)
  - long double (64 bits on 32-bit machines; 128 bits on 64-bit machines)
  - integer\*, real\*, complex\* promoted internally
  - addresses on 64-bit machines are 64-bits

# Word Size (Cont.)



#### **Implications**


- Run time errors
- Different results due to additional accuracy
- Integer variables that hold addresses may need to be changed
- Fortran-C interfaces may need modification
- Mixing implicit casts can give different results
- Adding constants (32-bit unsigned int) to long

#### Remedy

- Use integer\*8 to store addresses on 64-bit machines
- Use #if directives for bit sensitive areas of code
- C routines called by Fortran where variables are passed by reference must be modified to hold 64-bit addresses (no problem if *pointers* are defined)
- In C, always use *sizeof* to get size of variables

726-PPAJWays define types in Fortran and cast variables in C

# **Operating System**




#### **Compatibilities**

- Binary compatible (an executable created on 32-bit machine can run on 64-bit machine)
- Compiler switch that forces 32-bit programs to run in 32-bit mode on 64
   -bit machines (at the expense of performance)

#### **Incompatiblities**

- Cannot mix objects and Dynamic Shared Objects (DSOs) produced by 32-bit compilers with objects and DSOs produced by 64-bit compilers or vice versa
- Access to kernal data structures (kmem) must be ported to 64-bit environment
- IRIX GL does not yet have 64-bit support

# **Language Extensions**



- Project has suggested guidelines for language extensions for C and Fortran 77
- It is best not to use extensions for better portability
- Fortran 90 interpretation may be different from that of Fortran 77 for the following situations:
  - Fortran 90 has more intrinsic functions and can cause name collision (could be minimal)
  - If a named variable is not in a common block is initialized in a DATA statement, it has the SAVE attribute in Fortran 90
  - Input record is padded with as many blanks as necessary to satisfy the input item and the corresponding format. Not so in Fortran 77.
  - Fortran 77 permits a processor to supply extra precision for a real constant when it is used to initialize a DOUBLE PRECISION data object in a DATA statement. Fortran 90 does not permit this.

# Tips For Creating Portable Programs



- Keep portability in mind when developing code
- Good programming practice is essential
- Document areas in code that are bit sensitive (also use #if def)
- Avoid vendor specific extensions
- Don't make any assumption regarding pagesize (e.g. using mmap() and specifying the address). Use getpagesize().
- Use POSIX compliant compilers fort77 and c89 during development
- Consult a porting and transition guide (e.g. MIPSpro 64-Bit Porting and Transition Guide from Silicon Graphics, Inc.)
- Early prototyping can detect problem areas